

FINLUX

22FLHX841U



TECHNICAL SPECIFICATIONS

Cabinet

- Size : 22"

Display

- Display format : 16:9 (wide)
- HD Ready 1080 (Full HD)
- Resolution : 1920x1080
- Brightness : 300~400 cd/m2
- Contrast ratio : 1000:1
-

Receiving System

- Tuner: Analog / Digital (MPEG-4).
- Video standards : PAL, Secam, B/G, D/K,I, Secam L/L
- Colour system : PAL, Secam, NTSC 3.58, NTSC 4.43
- Tuner bands : VHF, UHF, Cable.
-
-
-
-

USB Play / Record

-
-
-
-
-

Specifications

- Touch buttons
- Automatic program sorting (APS), AUTO SEARCH (ATS)
- Program Storage Capacity (analog) : 200.
- Teletext page memory : 1000 page
- NTSC playback
- Multi language menu support
- Sleep Timer
- Child Lock

Picture & Sound Technology

- 3D Comb filter
- Hotel Mode (Passive)
- Equalizer (5 BAND)
- Dolby Digital Plus(DD+)
- Automatic volume limiter (AVL)
- 2 x 2.5W speakers (%10 THD).

Connectors

- 1 x HDMI (HDCP)
- Headphone jack
- PC VGA video and audio inputs via YPbPr DEFAULT
- 1 x SCART
- Composite video input (YPbPr)
- COMMON INTERFACE (PCMCIA SLOT FOR PAY CHANNELS)
- Antenna connection IEC (75 ohm coaxial)
- Common Interface Slot
-
-
-

Power Supply

- Power : 220 - 240VAC, 50 Hz
- Stand By power consumption : Less than 1W

Dimensions (mm) / Weight (kg)

-
-
-
-

FINLUX



TECHNICAL SPECIFICATIONS

Cabinet

- Size : 26"

Display

- Display format : 16:10 (Wide)
- HD Ready 1080p (Full HD)
- Resolution : 1920x1200
- Brightness : 300 cd/m2
- Contrast ratio : 1000 : 1
- Dynamic contrast ratio : 100.000 : 1

Receiving System

- Built-in HD DVB - T tuner (MPEG 4 compatible)
- 7 days electronic program guide (EPG)
- OAD (Over air download)
- MHEG v1.06 compliant
- Multi language audio & subtitle support
- Video standards: PAL, Secam, B/G, D/K,I, Secam L/L'
- Colour system: PAL, Secam, NTSC 3.58, NTSC 4.43
- Tuner bands: VHF, UHF, S-Canal, Hyperband

USB Play / Record

- USB2.0
- MPEG layer 1/2/3 , XviD version 1.1.2, MPEG4 (.avi), OGG Vorbis
- PCM / MP3 / WMA (upto 320 kbps)
- GIF BMP JPG (upto 179 mega pixel) progressive and baseline
- .ssa .ass .srt .smi sub .psb external subtitle support

Specifications

- Touch buttons
- Automatic program sorting (APS)
- 200 preset analogue, 2000 preset IDTV channels memory
- Teletext page memory : 1000 page
- PIP (Picture in Picture), PAP (Picture and Picture)
- 4:3 - 16:9 Auto switch (WSS)
- Sleep timer
- Child Lock

Picture & Sound Technology

- 3D Comb filter
- SRS Trusurround XT
- 5 Band equalizer
- Nicam / A2 stereo
- Automatic volume limiter (AVL)
- 2x10W speakers

Connectors

- 4 x HDMI sockets
- SPDIF Digital coaxial and optical audio output
- Audio line In (2xRCA) audio line out (2xRCA)
- Headphone jack
- S-Video reception over SCART
- PC VGA video and audio inputs
- 2 x SCART input sockets
- Composite video input (YPbPr)
- Common Interface Slot
- Antenna connection IEC (75 ohm coaxial)
- Active antenna support

Power Supply

- Maximum power consumption : 75W
- Stand By power consumption : Less than 0,25W

Dimensions (mm) / Weight (kg)

- Dimensions (with TV foot) : 607x165x480mm
- Dimensions (without TV foot) : 607x49x438mm
- Weigth (with TV foot) : 8,4kg
- Weigth (without TV foot) : 8,1kg